

INT3075 Programming and Problem Solving for Mathematics

More on Files and Exceptions

What we already know

- Files are bytes on disk. Two types, text and binary (we are working with text)
- `open` creates a connection between the disk contents and the program
- different modes of opening a file, 'r', 'w', 'a'
- files might have different encodings (default is utf_8)

more of what we know

- all access, reading or writing, to a text file is by the use of strings
- iteration via a `for` loop gathers info from a file opened for reading one line at a time
- we write to a file opened for writing using the `print` function with an argument `file=`



Code Listing

L11-1.py

Review

```
1 # Prompt for three values: input file, output file, search string.
2 # Search for the string in the input file, write results to the
3 # output file
4
5 import sys
6 def process_file(i_file, o_file, a_str):
7     ''' if the a_str is in a line of i_file, add stars
8         to the a_str in line, write it out with the
9         line number to o_file '''
10    line_count_int = 1
11    for line_str in i_file:
12        if a_str in line_str:
13            new_line_str = line_str.replace(a_str, '***'+a_str)
14            print('Line {}: {}'.format(line_count_int, new_line_str),\
15                file=o_file)
16            line_count_int += 1
17
18    try:
19        in_file_str = input("File to search:")
20        in_file = open(in_file_str, 'r', encoding='utf_8')
21    except IOError:
22        print('{} is a bad file name'.format(in_file_str))
23        sys.exit()
24
25    out_file_str = input("File to write results to:")
26    out_file = open(out_file_str, 'w')
27    search_str = input("Search for what string:")
28    process_file(in_file, out_file, search_str)
29    in_file.close()
30    out_file.close()
```

results, searching for "This"

inFile.txt	outFile.txt
This is a test	Line 1: ***This is a test
This is only a test	
Do not pass go	Line 2: ***This is only a test
Do not collect \$200	

More ways to read

- `my_file.read()`
 - Reads the entire contents of the file as a string and returns it. It can take an optional argument integer to limit the read to N bytes, that is `my_file.read(N)`
- `my_file.readline()`
 - Delivers the next line as a string.
- `my_file.readlines()` # note plural
 - Returns a **single list** of all the lines from the file

example file

We'll work with a file called `temp.txt` which has the following file contents

```
First Line
```

```
Second Line
```

```
Third Line
```

```
Fourth Line
```



```
>>> temp_file = open("temp.txt", "r")           # open file for reading
>>> first_line_str = temp_file.readline()      # read exactly one line
>>> first_line_str
'First line\n'
>>> for line_str in temp_file:                # read remaining lines
        print(line_str)
```

Second line

Third line

Fourth line

```
>>> temp_file.readline()                       # file read, return empty str
''
>>> temp_file.close()
```

```
>>> temp_file = open("temp.txt", "r") # open file for reading
>>> temp_file.read(1) # read 1 char
'F'
>>> temp_file.read(2) # read the next 2 chars
'ir'
>>> temp_file.read() # read remaining file
'st line\nSecond line\nThird line\nFourth line\n'
>>> temp_file.read(1) # file read, return empty string
''
>>> temp_file.close()
```

```
>>> temp_file = open("temp.txt","r") # open file for reading
>>> file_contents_list = temp_file.readlines() # read all file lines into a list
>>> file_contents_list
['First line\n', 'Second line\n', 'Third line\n', 'Fourth line\n']
>>>
```

More ways to write

- Once opened, you can write to a file (if the mode is appropriate):
 - `my_file.write(s)`
 - Writes the string `s` to the file
 - `my_file.writelines(lst)`
 - write a ***list of strings*** (one at a time) to the file

```
>>> word_list = ['First', 'Second', 'Third', 'Fourth']
>>> out_file = open('outFile.txt', 'w')
>>> for word in word_list:
...     out_file.write(word + ' line\n')
...
>>> out_file.close()
>>>
```



Universal New Line

Different OS's, different format


- Each operating system (Windows, OS X, Linux) developed certain standards for representing text
- In particular, they chose different ways to represent the end of a file, the end of a line, etc.

Operating System	Character Combination
Unix & Mac OS X	'\n'
MS Windows	'\r\n'
Mac (pre-OS X)	'\r'

TABLE 14.1 End-of-Line Characters

Universal new line

- To get around this, Python provides **by default** a special file option to deal with variations of OS text encoding called Universal new line
- you can over-ride this with an option to `open` called `newline=`
 - look at the docs for what this entails.



Working with a file

The current file position

- Every file maintains a ***current file position***.
- It is the current position in the file, and indicates what the file will read next
- Is set by the mode table above

Remember the file object buffer

- When the disk file is opened, the contents of the file are copied into the buffer of the file object
- Think of the file object as a very big list, where every index is one of the pieces of information of the file
- The current position is the present index in that list

File object buffer




FIGURE 14.1 Current file position.

the tell() method

- The `tell()` method tells you the current file position
- The positions are in bytes (think characters for UTF-8) from the beginning of the file

```
my_file.tell() => 42L
```

the seek() method

- the `seek()` method updates the current file position to a new file index (in bytes offset from the beginning of the file)
- `fd.seek(0)` # to the beginning of the file
- `fd.seek(100)` # 100 bytes from beginning

counting bytes is a pain

- counting bytes is a pain
- `seek` has an optional argument set:
 - 0: count from the beginning
 - 1: count for the current file position
 - 2: count from the end (backwards)

every read moves current forward

- every read/readline/readlines moves the current pos forward
- when you hit the end, every read will just yield '' (empty string), since you are at the end
 - no indication of end-of-file this way!
- you need to seek to the beginning to start again (or close and open, seek is easier)


```
>>> test_file = open('temp.txt','r')
>>> test_file.tell()           # where is the current file position?
0
>>> test_file.readline()      # read first line
'First Line\n'
>>> test_file.tell()         # where are we now?
11
>>> test_file.seek(0)        # go to beginning
0
>>> test_file.readline()     # read first line again
'First Line\n'
>>> test_file.readline()     # read second line
'Second Line\n'
>>> test_file.tell()        # where are we now?
23
>>> test_file.seek(0,2)      # go to end
46
>>> test_file.tell()        # where are we now?
46
>>> test_file.readline()     # try readline at end of file: nothing there
''
>>> test_file.seek(11)      # go to the end of the first line (see tell above)
11
>>> test_file.readline()     # when we read now we get the second line
'Second Line\n'
>>> test_file.close()
>>> test_file.readline()     # Error: reading after file is closed
Traceback (most recent call last):
  File "<pysshell#65>", line 1, in <module>
    test_file.readline()
ValueError: I/O operation on closed file.
>>>
```

`with` statement

`open` and `close` occur in pairs (or should)
so Python provides a shortcut, the `with`
statement

- creates a context that includes an exit
which is invoked automatically
- for files, the exit is to close the file


```
with expression as variable:  
    suite
```

File is closed automatically when the suite ends

```
>>> with open('temp.txt') as temp_file:
...     temp_file.readlines()
...
['First line\n', 'Second line\n', 'Third line\n', 'Fourth line\n']
>>>
```

read(size=1)

- you can use the `read()` method to read just one byte at a time, and in combination with `seek` move around the file and “look for things”. Once current is set, you can begin reading again



More on CSV files

spreadsheets

- The spreadsheet is a very popular, and powerful, application for manipulating data
- Its popularity means there are many companies that provide their own version of the spreadsheet
- It would be nice if those different versions could share their data

CSV, basic sharing

- A basic approach to share data is the comma separated value (CSV) format
 - it is a text format, accessible to all apps
 - each line (even if blank) is a row
 - in each row, each value is separated from the others by a comma (even if it is blank)
 - cannot capture complex things like formula

Spread sheet and corresponding CSV file

Name	Exam1	Exam2	Final Exam	Overall Grade
Bill	75.00	100.00	50.00	75.00
Fred	50.00	50.00	50.00	50.00
Irving	0.00	0.00	0.00	0.00
Monty	100.00	100.00	100.00	100.00
Average				56.25

FIGURE 14.2 A simple spreadsheet from Microsoft Excel 2008.

```
Name,Exam1,Exam2,Final Exam,Overall Grade
Bill,75.00,100.00,50.00,75.00
Fred,50.00,50.00,50.00,50.00
Irving,0.00,0.00,0.00,0.00
Monty,100.00,100.00,100.00,100.00

Average,,,,56.25
```


Even CSV isn't universal

- As simple as that sounds, even CSV format is not completely universal
 - different apps have small variations
- Python provides a module to deal with these variations called the csv module
- This module allows you to read spreadsheet info into your program

csv reader

- import the csv module
- open the file as normally, creating a file object.
- create an instance of a csv reader, used to iterate through the file just opened
 - you provide the file object as an argument to the constructor
- iterating with the reader object yields a row as a list of strings



Code Listing

L11-2.py

(and output)

```
import csv
workbook_file = open('Workbook1.csv', 'r')
workbook_reader = csv.reader(workbook_file)

for row in workbook_reader:
    print(row)

workbook_file.close()
```

```
>>>
['Name', 'Exam1', 'Exam2', 'Final Exam', 'Overall Grade']
['Bill', '75.00', '100.00', '50.00', '75.00']
['Fred', '50.00', '50.00', '50.00', '50.00']
['Irving', '0.00', '0.00', '0.00', '0.00']
['Monty', '100.00', '100.00', '100.00', '100.00']
[]
['Average', '', '', '', '56.25']
>>>
```


things to note

- Universal new line is working by default
 - needed for this worksheet
- A blank line in the CSV shows up as an empty list
- empty column shows up as an empty string in the list


csv writer

much the same, except:

- the opened file must have write enabled
- the method is `writerow`, and it takes a ***list of strings*** to be written as a row



This code listing is a good example of reading, modifying and then writing out a CSV file that could be read by a spreadsheet



os module

What is the os module

- The `os` module in Python is an interface between the operating system and the Python language.
- As such, it has many sub-functionalities dealing with various aspects.
- We will look mostly at the file related stuff

What is a directory/folder?

- Whether in Windows, Linux or on OS X, all OS's maintain a ***directory structure***.
- A directory is a container of files or other directories
- These directories are arranged in a hierarchy or tree

Tree

- it has a **root** node, with **branch** nodes, ends in **leaf** nodes
- the directory structure is hierarchy (tree)




FIGURE 14.4 Directory tree with path /punch/python/ex1.py, marked with arrows.

Directory tree

- Directories can be organized in a hierarchy, with the root directory and subsequent branch and leaf directories
- Each directory can hold files or other directories

file path is a path through the tree


A path to a file is a path through the hierarchy to the node that contains a file

```
/gary/python/code/myCode.py
```

- path is from the root node /, to the bill directory, to the python directory, to the code directory where the file myCode.py resides

the / in a path

- think of / as an operator, showing something is a directory
- follow the path, the leaf is either a directory or file



a path String

- a valid path string for python is a string which indicates a valid path in the directory structure
- Thus `'/Users/gary/python/code.py'` is a valid path string

different 'paths' for different os

- It turns out that each OS has its own way of specifying a path
 - C:\gary\python\myFile.py
 - /Users/gary/python/myFile.py
- Nicely, Python knows that and translates to the appropriate OS

Two special directory names

- The directory name `'.'` is shortcut for the name of the current directory you are in as you traverse the directory tree
- The directory name `'..'` is a shortcut for the name of the parent directory of the current directory you are in

Some os commands

- `os.getcwd()` Returns the full path of the current working directory
- `os.chdir(path_str)` Change the current directory to the path provided
- `os.listdir(path_str)` Return a list of the files and directories in the path (including `'.'`)

```
>>> import os                                # load the os package
>>> os.chdir("/punch/python")                 # change to the example starting point
>>> os.getcwd()                               # check that we are there
'/punch/python'
>>> os.listdir(".") # list contents of current directory, indicated by "."
['ex1.py', 'ex2.py', 'one.txt']
>>> dir_list = os.listdir(".")                # we can give that list a name
>>> dir_list
['ex1.py', 'ex2.py', 'one.txt']
>>> os.listdir("/punch")                      # list the contents at some path
['Docs', 'python']
```

Some more os commands

- `os.rename(source_path_str, dest_path_str)` Renames a file or directory
- `os.mkdir(path_str)` make a new directory. So `os.mkdir('/Users/bill/python/new')` creates the directory `new` under the directory `python`.
- `os.remove(path_str)` Removes the file
- `os.rmdir(path_str)` Removes the directory, but the directory must be empty


the walk function

- `os.walk(path_str)` Starts at the directory in `path_str`. It yields three values:
 - `dir_name`, name of the current directory
 - `dir_list`, list of subdirectories in the directory
 - `files`, list of files in the directory
- If you iterate through, walk will visit every directory in the tree. Default is top down

Walk example

```
>>> os.getcwd()                # check our starting point
'/punch'
>>> for dir_name, dirs, files in os.walk("."): # "walk" in the current directory
    print(dir_name, dirs, files)

. ['Docs', 'python'] [] # current directory, list of 2 subdirectories, no files
./Docs [] ['three.txt', 'two.txt'] # Docs directory, no subdirectories, 3 files
./python [] ['ex1.py', 'ex2.py', 'one.txt'] # directory, no subdirectories, 3 files
>>>
```



os.path module

os.path module

allows you to gather some info on a path's existence

- `os.path.isfile(path_str)` is this a path to an existing file (T/F)
- `os.path.isdir(path_str)` is this a path to an existing directory (T/F)
- `os.path.exists(path_str)` the path (either as a file or directory) exists (T/F)

os.path names

assume `p = '/Users/bill/python/myFile.py'`

- `os.path.basename(p)` **returns** `'myFile.py'`
- `os.path.dirname(p)` **returns**
`'/Users/bill/python'`
- `os.path.split(p)` **returns**
`['Users/bill/python', 'myFile.py']`
- `os.path.splitext(p)` **returns**
`'/Users/bill/python/myFile', '.py'`
- `os.path.join(os.path.split(p)[0], 'other.py')` **returns** `'/Users/bill/python/other.py'`



Code Listing

L11-4.py

Utility to find strings in files

- The main point of this function is to look through all the files in a directory structure and see if a particular string exists in any of those files
- Pretty useful for mining a set of files
- lots of comments so you can follow

```
def check(search_str,count,files_found_list,dirs_found_list):
    for dirname,dir_list,file_list in os.walk("."):    # walk the subtree
        for f in file_list:
            if os.path.splitext(f)[1] == ".txt":    # if it is a text file
                count = count + 1                    # add to count of files examined
                a_file = open(os.path.join(dirname,f),'r')    # open text file
                file_str = a_file.read()                # read whole file into string

                if search_str in file_str:            # is search_str in file?
                    filename = os.path.join(dirname,f)    # if so, create path
                                                            # for file
                    files_found_list.append(filename)    # and add to file list
                    if dirname not in dirs_found_list:    # if directory is not
                        dirs_found_list.append(dirname)    # and directory list
                a_file.close()

return count
```



More Exceptions

What we already know

try-except suite to catch errors:

```
try:
```

```
    suite to watch
```

```
except ParticularError
```

```
    error suite
```

more of what we know

- `try` suite contains code that we want to watch:
 - if an error occurs the try suite stops and looks for an `except` suite that can handle the error
- `except` suite has a particular error it can handle and a suite of code for handling that error

Error Flow




FIGURE 14.5 Exception flow.



Code Listing

L11-5.py

```

1 try:
2     print("Entering the try suite")
3     dividend = float(input("Provide a dividend to divide:"))
4     divisor = float(input("Provide a divisor to divide by:"))
5     result = dividend/divisor
6     print("{:2.2f} divided by {:2.2f} yields {:2.2f}".\
7         format(dividend,divisor,result))
8 except ZeroDivisionError:
9     print("Divide by 0 error")
10 except ValueError:
11     print("Value error, could not convert to a float")
12
13 print("Continuing on with the rest of the program")

```

>>>

Entering the **try** suite

Provide a dividend to divide:10

Provide a divisor to divide by:2

10.00 divided by 2.00 yields 5.00

Continuing on with the rest of the program

>>> ===== RESTART =====

>>>

Entering the **try** suite

Provide a dividend to divide:10

Provide a divisor to divide by:a

Value error, could **not** convert to a *float*

Continuing on with the rest of the program

Continuing ...

```
>>> ===== RESTART =====
>>>
Entering the try suite
Provide a dividend to divide:10
Provide a divisor to divide by:0
Divide by 0 error
Continuing on with the rest of the program
>>> ===== RESTART =====
>>>
Entering the try suite
Provide a dividend to divide:

Traceback (most recent call last):
  File "/Users/bill/book/v3.5/chapterExceptions/divide.py", line 3, in <module>
    dividend = float(input("Provide a dividend to divide:"))
KeyboardInterrupt
>>>
```

Check for specific exceptions

- Turns out that you don't have to check for an exception type. You can just have an exception without a particular error and it will catch anything
- That is a bad idea. How can you fix (or recover from) an error if you don't know the kind of exception
- Label your exceptions, all that you expect!

What exceptions are there?

- In the present Python, there is a set of exceptions that are pre-labeled.
- To find the exception for a case you are interested in, it's easy enough to try it in the interpreter and see what comes up
- The interpreter tells you what the exception is for that case.

BaseException

- +– SystemExit
- +– KeyboardInterrupt
- +– GeneratorExit
- +– Exception
 - +– StopIteration
 - +– ArithmeticError
 - | +– FloatingPointError
 - | +– OverflowError
 - | +– ZeroDivisionError
 - +– AssertionError
 - +– AttributeError
 - +– BufferError
 - +– EnvironmentError
 - | +– IOError
 - | +– OSError
 - | +– WindowsError
 - | +– VMSError
 - +– EOFError
 - +– ImportError
 - +– LookupError
 - | +– IndexError
 - | +– KeyError
 - +– MemoryError
 - +– NameError
 - | +– UnboundLocalError
 - +– ReferenceError
 - +– RuntimeError
 - | +– NotImplementedError
 - +– SyntaxError
 - | +– IndentationError
 - | +– TabError
 - +– SystemError
 - +– TypeError
 - +– ValueError
 - | +– UnicodeError
 - | +– UnicodeDecodeError
 - | +– UnicodeEncodeError
 - | +– UnicodeTranslateError
 - +– Warning
 - +– DeprecationWarning
 - +– PendingDeprecationWarning
 - +– RuntimeWarning
 - +– SyntaxWarning
 - +– UserWarning
 - +– FutureWarning
 - +– ImportWarning
 - +– UnicodeWarning
 - +– BytesWarning
 - +– ResourceWarning

FIGURE 14.6 Python exceptions.

Examples

```
>>> 100/0
```


```
Traceback (most recent call last):
```

```
File "<pyshell#1>", line 1, in <module>
```

```
100/0
```

```
ZeroDivisionError: integer division or modulo by zero
```

error
names
CAPS
matter!




```
>>> open('badFileName')
```

```
Traceback (most recent call last):
```

```
File "<pyshell#2>", line 1, in <module>
```

```
open('badFileName')
```

```
IOError: [Errno 2] No such file or directory: 'badFileName'
```



Philosophy of Exception Handling

Dealing with problems

Two ways to deal with exceptions

- ***LBYL***: Look Before you Leap
- ***EAFP***: Easier to Ask Forgiveness than Permission (famous quote by Grace Hopper)

Look Before You Leap

- By this we mean that before we execute a statement, we check all aspects to make sure it executes correctly:
 - if it requires a string, check that
 - if it requires a dictionary key, check that
- Tends to make code messy. The heart of the code (what you want it to do) is hidden by all the checking.

Easier to Ask Forgiveness than Permission

- By this we mean, run any statement you want, no checking required
- However, be ready to “clean up any messes” by catching errors that occur
- The `try` suite code reflects what you want to do and the `except` code what you want to do on error. Cleaner separation!

Python likes EAFP

- Code Python programmers support the ***EAFP*** approach:
 - run the code, let the `except` suites deal with the errors. Don't check first.



Code Listing

L11-6.py

*# check whether int conversion will raise an error, two examples.
Python Idioms, <http://jaynes.colorado.edu/PythonIdioms.html>*

#LBYL, test for the problematic conditions

```
def test_lbyl (a_str):  
    if not isinstance(a_str, str) or not a_str.isdigit:  
        return None  
    elif len(a_str) > 10:      #too many digits for int conversion  
        return None  
    else:  
        return int(a_str)
```

#EAFP, just try it, clean up any mess with handlers

```
def test_eafp(a_str):  
    try:  
        return int(a_str)  
    except (TypeError, ValueError, OverflowError): #int conversion failed  
        return None
```



Extensions to the basic Exception Model

finally suite

- you can add a `finally` suite at the end of the `try/except` group
- the `finally` suite is run as you exit the `try/except` suite, ***no matter whether an error occurred or not.***
 - even if an exception raised in the `try` suite was not handled!
- Gives you an opportunity to clean up as you exit the `try/except` group

`finally` and `with`

`finally` is related to a `with` statement:

- creates a context (the `try` suite)
- has an exit, namely execute the `finally` suite

else

- One way to think about things is to think of the `try` as a kind of condition (an exception condition) and the `excepts` as conditional clauses
- if an exception occurs then you match the exception
- the `else` clause covers the non-exception condition. It runs when the `try` suite does not encounter an error.

The whole thing

```
try:  
    code to try  
except PythonError1:  
    exception code  
except PythonError2:  
    exception code  
except:  
    default except code  
else:  
    non exception case  
finally:  
    clean up code
```




Code Listing

L11-7.py

all aspects of exceptions

```
def process_file(data_file):  
    """Print each line of a file with its line number."""  
    count = 1  
    for line in data_file:  
        print('Line ' + str(count) + ': ' + line.strip())  
        count = count + 1  
  
while True:    # loop forever: until "break" is encountered  
    filename = input('Input a file to open: ')  
    try:  
        data_file = open(filename)  
    except IOError:    # we get here if file open failed  
        print('Bad file name; try again')  
    else:  
        # no exception so let's process the file  
        print('Processing file',filename)  
        process_file(data_file)  
        break    # exit "while" loop (but do "finally" block first)  
    finally:    # we get here whether there was an exception or not  
        try:  
            data_file.close()  
        except NameError:  
            print('Going around again')  
  
print('Line after the try-except group')
```



Raising and creating your own exceptions

invoking yourself, `raise`

- You can also choose to invoke the exception system anytime you like with the `raise` command

```
raise MyException
```

- you can check for odd conditions, `raise` them as an error, then catch them
- they must be part of the existing exception hierarchy in Python

Non-local catch

- Interestingly, the `except` suite does not have to be right next to the `try` suite.
- In fact, the `except` that catches a `try` error can be in another function
- Python maintains a chain of function invocations. If an error occurs in a function and it cannot catch it, it looks to the function that called it to catch it

Make your own exception

- You can make your own exception.
- Exceptions are classes, so you can make a new exception by making a new subclass:

```
class MyException (IOError):  
    pass
```

- When you make a new class, you can add your own exceptions.



Code Listing

L11-8.py

Part 1

```
1 import string
2
3 # define our own exceptions
4 class NameException (Exception):
5     ''' For malformed names '''
6     pass
7 class PasswordException (Exception):
8     ''' For bad password '''
9     pass
10 class UserException (Exception):
11     ''' Raised for existing or missing user '''
12     pass
13
14 def check_pass(pass_str, target_str):
15     """Return True, if password contains characters from target."""
16     for char in pass_str:
17         if char in target_str:
18             return True
19     return False
20
21 class PassManager(object):
22     """A class to manage a dictionary of passwords with error checking."""
23     def __init__(self, init_dict=None):
24         if init_dict==None:
25             self.pass_dict={}
```

Part 2

```
26     else:
27         self.pass_dict = init_dict.copy()
28
29 def dump_passwords(self):
30     return self.pass_dict.copy()
31
32 def add_user(self,user):
33     """Add good user name and strong password to password dictionary."""
34     if not isinstance(user,str) or not user.isalnum():
35         raise NameException
36     if user in self.pass_dict:
37         raise UserException
38     pass_str = input('New password:')
39     # strong password must have digits, uppercase and punctuation
40     if not (check_pass(pass_str, string.digits) and\
41             check_pass(pass_str, string.ascii_uppercase) and\
42             check_pass(pass_str, string.punctuation)):
43         raise PasswordException
44
45 def validate(self,user):
46     """Return True, if valid user and password."""
47     if not isinstance(user,str) or not user.isalnum():
48         raise NameException
49     if user not in self.pass_dict:
50         raise UserException
51     password = input('Passwd:')
52     return self.pass_dict[user]==password
```